

SP SANPING

广州市三平机械有限公司
GUANGZHOU SANPING MACHINERY CO.,LTD.



三角型 SIDE TYPE



静音型 SILENT TYPE



直角型 RIGHT-ANGLE TYPE

Companies and a number of spare parts business has long-term supply agreement, equipped with various models of the hammer supporting spare parts: piston, inner sleeve, jacket, round pin, flat pin, flange, flange screws, nitrogen table, inflatable blocking valve, exhaust valve, grease fittings, plastic, rubber stopper.

破碎锤剖面图解

Customer credit standing is the source of enterprise development

破碎锤系列



三角型 SIDE TYPE / 直角型 RIGHT-ANGLE TYPE / 静音型 SILENT TYPE 技术参数

Model	Unit	SP-45	SP-53	SP-68	SP-75	SP-85	SP-100	SP-125	SP-135
工作重量 Working Weight	kg	150	192	245	390	467	750	1080	1570
工作压力 Operating Pressure	bar	90-120	90-120	95-130	95-130	130-150	150-170	150-170	160-180
工作流量 Bequined Oil Flow	l/min	26-41	26-41	30-45	40-80	45-85	80-110	90-120	125-150
冲击频率 Bolw Per Minute	bpm	550-950	550-950	450-750	450-950	400-800	450-750	400-530	400-490
软管直径 Hose Diameter	inch	1/2	1/2	1/2	3/4	3/4	3/4	1	1
钎杆直径 Tool Diameter	mm	45	53	68	80	85	100	125	135
挖掘机 Excavator	ton	0.8-4	1.2-4	4-6	5-9	6-11	8-15	12-18	18-25

Model	Unit	SP-140	SP-150	SP-155	SP-165	SP-175	SP-190	SP-210
工作重量 Working Weight	kg	1750	2116	2300	2610	3788	4130	5070
工作压力 Operating Pressure	bar	160-180	160-180	160-190	160-190	160-180	160-180	160-180
工作流量 Bequined Oil Flow	l/min	125-150	150-210	160-180	180-240	210-290	230-290	230-290
冲击频率 Bolw Per Minute	bpm	320-660	300-450	300-650	300-600	200-350	200-350	200-330
软管直径 Hose Diameter	inch	1	1	1	1 1/4	1 1/4	3/2	3/2
钎杆直径 Tool Diameter	mm	140	150	155	165	175	190	210
挖掘机 Excavator	ton	23-28	25-30	25-35	32-45	40-55	50-80	60-80

We produce our goods with the best quality.



body ass'y 本体



BACK HEAD 上缸体



Cylinder 中缸



Front head 下缸体



Accumulator and its components
蓄能器及其组件



Thrust bush, front cover
内、外衬套



Seal housing 活塞缸套



Piston 活塞



Rod Pin 扁肖



Stop Pin 圆肖



Through bolts 通体螺栓



Side Bolt 侧板螺栓



Side Bolt 侧板螺栓



Side Bolt 侧板螺栓

破碎锤系列

 <p>Valve and valve core 换向阀及换向阀芯</p>	 <p>Steeling Cap 换向阀盖</p>	 <p>Mouting Pin 连接轴</p>
 <p>External seat 外置阀座</p>	 <p>NUT 贯穿螺栓组件</p>	 <p>Rubber Components 胶堵</p>
 <p>Gas Charging Adjuster 充气调节器</p>	 <p>Hex Socket Plug 高强度内六角螺栓</p>	 <p>Daemo Gas Charging Adjuster 大漠充气阀</p>
 <p>Valve Adjuster 调频螺栓</p>	 <p>Nipple Socket 对丝</p>	 <p>Nipple Adapter Plug 对丝接头</p>

CHISEL SELECTION



Blunt Type

Moil Type

Conical Point Type

V-Wedge Type

H-Wedge Type

Moil Point

This tool is appropriate for breaking oversized material and concrete pads where a chisel point may go through very quickly.

Flat Wedge

This tool is suitable for general breaking works where accurate control cut is not required.

Blunt

This tool is designed for the demolition of oversized rock and slabs.

CHARGING KIT

破碎锤系列



水山, 工兵, 古河油压表
SOOSAN,GB,FRD CHARGING KIT



韩宇, 大漠油压表
HANWOO,DAEMO CHARGING KIT



氮气瓶
NITROGON GAS BOLLTE



液压油管
HYDRAULIC HOSE